
SPECIFICATIONS

Dimensions in inches. Refer to installation/owner's manual for detailed specifications on installing this product. Hearth & Home Technologies reserves the right to update units periodically. Product installation must adhere strictly to instructions shipped with product.

Model	Front Width	Back Width	Height	Depth	Glass Size BTU/Hour Input
	Min. Unit Firebox Opening	Min. Unit Firebox Opening	Min. Unit Firebox Opening	Min. Unit Firebox Opening	
Escape-I3030	30-1/4	21-1/4 21-1/2	22-5/8 22-3/4	15-5/8 16-7/8	26-3/4 x 1836,000 (NG)
Escape-I3534-3/435		25-1/4 25-1/2	24-5/8 24-7/8	16-5/8 17-7/8	31-1/2 x 2040,000 (NG)

SPECIFICATION DETAILS



Efficiencies

Model	Steady State	AFUE	Canada EnerGuide
Escape-I30	85.8% NG	70.1% NG	68.8% NG
Escape-I35	85.8% NG	73.1% NG	72.9% NG

Btus will vary depending on the type of fuel used. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Actual product appearance, including flame may differ from image shown. Refer to the Owner's Manual for complete clearance requirements and specifications. Product specifications and pricing subject to change without notice. For testing and listing information please refer to the owners/installation manual.

*For select products: Heating capacity represents a well-insulated home with low ceilings in a mild climate. Heating capacity (in square footage) is a guideline only and may differ slightly due to climate, building construction and condition, amount and quality of insulation, location of the heater, and air movement in the room.